



2010

Проволока: LÖTTERS (Германия)

LÖTTERS Draht.

DIN EN ISO 9001:2000

LÖTTERS

: SC

- 900 - 1100 H/ ²;

- 1300 - 1500 H/ ².

5, 15, 17 ³ ;

0,50-0,55 ;

0,60-0,80

: NC



		1	
21	0,80	257	771
23	0,70	335	1005
24	0,60	456	1368
25	0,55	543	1629
26	0,50	657	1971

PS

	0,35 - 1,60	0,014 - 0,063
	0,35 – 0,70 - 0,02 / +0,00 0,75 – 1,60 - 0,02 / +0,01	0,014 – 0,023 - 0,0008 / +0,0000 0,030 – 0,063 - 0,0008 / - 0,0004
	: 900 – 1100 / ² : 1300 – 1500 / ²	130 – 160 PSI 10 ³ 190 – 220 PSI 10 ³
	EN 10016 C4D	
	C ? 0,06% - Si ? 0,05% - Mn ? 0,30 – 0,60% - P max. 0,035% - S max. 0,035% - Cr max. 0,20% - Ni max. 0,25% - Cu max. 0,30% -	
	3 15	

	1 . ()	
	80	80
0,5	0,40	0,45
0,5 – 1	0,50	0,55
1 – 2	0,55	0,60
2 – 3	0,60	0,65
3 – 4	0,65	0,70
4 – 5	0,70	0,75
5	0,75	0,80

2 – 5	0,40 – 0,50
5 – 10	0,55 – 0,65
10 – 15	0,70
15 – 20	0,70 – 0,80
20 – 25	0,80
25 – 45	0,80 – 0,85



	(C% ±0.07%)
	0,65 1,50
	0.05 - 0.07
, N/mm	650 ± 100
	540 700
	450 ± 5%

